


Incremental-Encoder IEV 44

Eglshalde 6
 D-78647 Trossingen
 Tel. +49 - (0) 74 25 / 228 - 0
 Fax +49 - (0) 74 25 / 228 - 33
<http://www.tr-electronic.de>
 Germany



- Incremental-interface
- Type with solid shaft
- Number of pulses per revolution 100, 1024
- Shaft diameter 6 mm

6.1

Characteristics

Supply voltage.....	11 ... 27 VDC, 5 ... 30 VDC
Current consumption without load	≤ 80 mA
Number of pulses per revolution	100, 1024
Outputs, 5 ... 30 VDC	
- Incremental signals.....	K1, K1 neg, K2, K2 neg
- Zero pulse.....	K0, K0 neg, 1 pulse per revolution
- Output frequency.....	≤ 50 kHz
- Supply voltage.....	5 ... 30 VDC
Outputs, 5 VDC	
- Incremental signals.....	K1, K1 neg, K2, K2 neg
- Zero pulse.....	K0, K0 neg, 1 pulse per revolution
- Output frequency.....	≤ 50 kHz
- Supply voltage.....	11 ... 27 VDC
Mechanically permissible speed	≤ 3.000 min ⁻¹ , short cycle time 10.000 min ⁻¹
Shaft load, at the shaft end	≤ 40 N axial, ≤ 40 N radial
Bearing life time	≥ 5,0 * 10 ⁹ revolutions
Shaft diameter in mm	6h7
Connection	radial cable outlet 1 m

Environmental conditions

Vibration, DIN EN 60068-2-6: 1996.....	≤ 100 m/s ² , sine 10-2000 Hz
Shock, DIN EN 60068-2-27: 1995.....	≤ 200 m/s ² , half-sine 11 ms
Working temperature.....	-10 °C ... +70 °C
Storage temperature.....	-30 °C ... +80 °C, dry
Relative humidity, DIN EN 60068-3-4: 2002.....	98 %, non condensing
Protection class, DIN EN 60529: 1991.....	IP 64
EMC.....	EN 61000-6-2: 2002, EN 61000-6-4: 2002

Order Information

No. of pulses per revolution	Supply voltage	Output level	Order No.
1024	11 ... 27 VDC	5 VDC	IEV44-00001
1024	5 ... 30 VDC	5 ... 30 VDC	IEV44-00002

Dimension drawing

